



: 0

- FINISH: HOT DIP GALVANIZE PER ASTM-A153 (LATEST REVISION). BASEPLATE TO BE PERPENDICULAR TO SHAFT AXIS (±1°) AND HOLE CENTERLINE TO BE CONCENTRIC (±, 188) TO SHAFT AXIS. STENCIL MIN. 1/2 IN. LETTERS MANUFACTURER'S NUMBER AFTER GALVANIZING.
- PILOT POINT AND SHAFT AXES TO BE CONCENTRIC (±, 125 FIM) IN LINE (±2°).

- PREHEAT, TUMBLEBLAST, HANDGRIND, AND CLEAN BASEPLATE,
 HELIX, AND PILOT POINT ON ALL WELDED PARTS.
 FLAMECUT IRREGULARITIES PERMISSIBLE: (1) VALLEYS NOT TO EXCEED
 3/32 IN. BELOW NOMINAL SURFACE LEVEL, (2) PEAKS OR POSITIVE
 IRREGULARITIES NOT TO EXCEED 1/32 IN. ABOVE NOMINAL SURFACE
 LEVEL OR INTERSECTIONS OF NOMINAL SURFACES.
 MANUFACTURER TO HAVE IN EFFECT INDUSTRY RECOGNIZED WRITTEN
 QUALITY CONTROL FOR ALL MATERIALS AND MANUFACTURING PROCESSES.
 BASEPLATE IS PERMANENTLY STAMPED WITH MANUFACTURER'S
 IDENTIFICATION "ABC" IN 1/2" LETTERS AND THE JULIAN DATE CODE
 IN 1/4" LETTERS.

- MATERIAL IS TO MEET THE FOLLOWING SPECIFICATIONS:

BASEPLATE: ASTM A36-(LATEST REVISION) STRUCTURAL STEEL

SHAFT: ASTM A252-(LATEST REVISION) GRADE 2, STEEL PIPE PILES. ALTERNATE MATERIAL: ASTM A53-(LATEST REVISION) TYPE E OR S, GRADE B, STEEL PIPE OR ASTM A500-(LATEST REVISION) GRADE B, STRUCTURAL STEEL TUBING.

HELLIX: ASTM A635-(LATEST REVISION) $3/8^{\prime\prime}$ THICK HOT ROLLED STEEL PLATE OR COIL.

PILOT POINT: ASTM A575-<LATEST REVISION) 1-1/4" STEEL BAR DIAMETER HOT ROLLED

- SPECIAL 1" DIAMETER HOT DIP GALVANIZED STUDS THREADED AT BOTH ENDS.
- FLAME CUT TWO SLOTS IN SHAFT PERPENDICALAR TO THE BASEPLATE. BASEPLATE PERMANENTLY MARKED TO INDICATE CABLEWAY OPENING IN SHAFT.



LIGHTING FOUNDATION T112-0294

ž

HELIX MUST BE FORMED BY MATCHING METAL DIE VIEW "A-A" (SIDE VIEW OF TRUE HELICAL FORM)

ALL RADIAL SECTIONS
NORMAL TO AXIS ±3°

3° PITCH

ALL RADIAL SECTIONS NORMAL TO AXIS ±3*