



=NOTES=

1. FINISH: PLAIN MILL FINISH.
2. MATERIAL SPECIFICATIONS:
 PIPE: STEEL PIPE PER ASTM A500 GRADE C, MIN YIELD 50 KSI.
 TOP PLATE: HOT ROLLED STEEL PER ASTM A572, GRADE 50
 CAP PLATE: HOT ROLLED STEEL PER ASTM A572, GRADE 50, 1/2" THICK.
 THREADBAR: WILLIAMS FORM GRADE 75 ALL-THREAD REBAR #14, LEFT-HAND.
 BOLT: HEX BOLT 3/4-10UNC-2A X 4-1/4" LONG PER SAE J429, GRADE 5.
3. FOR GALVANIZED FINISH PER ASTM A153 - (LATEST REVISION) PLEASE ADD "G" TO CATALOG NUMBER.

CATALOG NUMBER	"L"	"W"
C1501571	18.0	.203
C1501572	24.0	.203
C1501573	18.0	.276
C1501574	24.0	.276

CHANCE TOLERANCE CHART		HUBBELL POWER SYSTEMS	
CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, DISTRIBUTION OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS UNPUBLISHED. ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.			
TITLE RS2875 THREADED NEW CONSTRUCTION CAP		SIZE DWG NO. SB SA1501571	CAT / PART / ASST NO. SEE CHART
DO NOT SCALE THIS DRAWING	DWN BY JVH	DATE 4/5/16	SHEET 1 OF 1