



=NOTES=

1. FINISH: PLAIN MILL FINISH.
2. MATERIAL SPECIFICATIONS:  
 PIPE: 3/5" SCH. 80 STEEL PIPE PER ASTM A500 GRADE C, MIN YIELD 50 KSI.  
 SADDLE: HOT ROLLED STEEL PER ASTM A572, GRADE 50, 3/8" THICK.  
 CAP PLATE: HOT ROLLED STEEL PER ASTM A572, GRADE 50, 1/2" THICK.  
 THREADBAR: WILLIAMS FORM GRADE 75 ALL-THREAD REBAR #11, LEFT-HAND.  
 BOLT: HEX BOLT 3/4-10UNC-2A X 4-1/4" LONG PER SAE J429, GRADE 5.
3. FOR GALVANIZED FINISH PER ASTM A153 - (LATEST REVISION) PLEASE ADD "G" TO CATALOG NUMBER.

<b>CHANCE</b> TOLERANCE CHART		<b>HUBBELL POWER SYSTEMS</b>	
CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, DISTRIBUTION OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS UNPUBLISHED. ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.		TITLE <b>RS2875 THREADED NEW CONSTRUCTION CAP</b>	
SIZE SB SA1501578	DWG NO. SA1501578	CAT / PART / ASSY NO. C1501578	REV --
DO NOT SCALE THIS DRAWING	DWN BY BLJ	DATE 4/21/16	SHEET 1 OF 1