

- FINISH: HOT DIP GALVANIZE PER ASTM-A153 (LATEST REVISION).
 BASEPLATE TO BE PERPENDICULAR TO SHAFT AXIS (±1°) AND HOLE
 CENTERLINE CONCENTRIC (±, 188) TO SHAFT AXIS.
 STENCIL MIN. 1/2 IN. LETTERS MANUFACTURER'S NUMBER

- AFTER GALVANIZING.

 AFTER GALVANIZING.

 4. FLAME CUT TWO SLOTS IN SHAFT PERPENDICULAR TO THE BASEPLATE.

 5. PREHEAT, TUMBLEBLAST, HANDGRIND, AND CLEAN BASEPLATE,
 HELIX, AND PILOT POINT ON ALL WELDED AREAS.

 6. FLAMECUT IRREGULARITIES PERMISSIBLE: (1) VALLEYS NOT TO
 EXCEED 3/32 IN. BELOW NOMINAL SURFACE LEVEL, (2) PEAKS OR
 POSITIVE IRREGULARITIES NOT TO EXCEED 1/32 IN. ABOVE NOMINAL
 SURFACE LEVEL OR INTERSECTIONS OF NOMINAL SURFACES.

 7. MANUFACTURER TO HAVE IN EFFECT INDUSTRY RECOGNIZED WRITTEN
 QUALITY CONTROL FOR ALL MATERIALS AND MANUFACTURING PROCESSES.

 8. ALL MATERIAL IS TO BE NEW, UNUSED AND MILL TRACEABLE
 MEETING THE FOLLOWING SPECIFICATIONS:

BASEPLATE: ASTM A36-(LATEST REVISION) STRUCTURAL STEEL (CONFORM TO AASHTO TECH. BUL, #270).

- SHAFT: ASTM A252-(LATEST REVISION) GRADE 2, STEEL PIPE PILES. ALTERNATE MATERIAL: ASTM A53-(LATEST REVISION) TYPE E OR S, GRADE B, STEEL PIPE OR ASTM A500-(LATEST REVISION) GRADE B, STRUCTURAL STEEL TUBING.
- ASTM A635-(LATEST PLATE OR COIL. REVISION) 3/8" THICK HOT ROLLED STEEL
- CARRIAGE BOLT, SAE J429 GRADE 3/4-10UNC-2A PER ANSI B-18, 5, 5,
- مِ BASEPLATE IS PERMANENTLY STAMPED WITH MANUFACTURER'S IDENTIFICATION "ABC" IN 1/2" LETTERS AND DATE CODE IN 1/4" LETTERS.
- 10. BASEPLATE PERMANENTLY MARKED TO INDICATE CABLEWAY OPENING IN SHAFT.

LIGHTING F

