



HELIX MUST BE FORMED BY MATCHING METAL DIE (SIDE VIEW OF TRUE HELICAL FORM) LIGHTING FOUNDATION CAT, NO. T112-0160

\subseteq ITES 1

- ūΗ FINISH: HOT DIP GALVANIZE PER ASTM-A153 (LATEST REVISION).
 BASEPLATE TO BE PERPENDICULAR TO SHAFT AXIS (±1°) AND HOLE
 CENTERLINE CONCENTRIC (±, 188) TO SHAFT AXIS.
 STENCIL MIN. 1/2 IN. LETTERS MANUFACTURER'S NUMBER
 AFTER GALVANIZING.
 PILOT POINT AND SHAFT AXES TO BE CONCENTRIC (±, 125 FIM) AND

ல் வ 4. ω

- IN LINE (±2*).

 IN LINE (±2*).

 S. FLAME CUT TWO SLOTS IN SHAFT PERPENDICULAR TO THE BASEPLATE.

 6. PREHEAT, TUMBLEBLAST, HANDGRIND, AND CLEAN BASEPLATE.

 7. FLAMECUT IRREGULARITIES PERMISSIBLE: (1) VALLEYS NOT TO EXCEED 3/32 IN. BELOW NOMINAL SURFACE LEVEL, (2) PEAKS OR POSITIVE IRREGULARITIES NOT TO EXCEED 1/32 IN. ABOVE NOMINAL SURFACES.

 8. MANUFACTURER TO HAVE IN EFFECT INDUSTRY RECOGNIZED WRITTEN QUALITY CONTROL FOR ALL MATERIALS AND MANUFACTURING PROCESSES.

 9. ALL MATERIAL IS TO BE NEW, UNUSED AND MILL TRACEABLE

9 φ

- BASEPLATE ASTM A36-(LATEST REVISION) STRUCTURAL STEEL (CONFORM TO AASHTO TECH. BUL. #270).
- SHAFT: ASTM A252-(LATEST REVISION) GRADE 2, STEEL PIPE PILES. ALTERNATE MATERIAL: ASTM A53-(LATEST REVISION) TYPE E OR S, GRADE B, STEEL PIPE OR ASTM A500-(LATEST REVISION) GRADE B, STRUCTURAL STEEL TUBING.
- HELLIX: ASTM A635COIL. THICK HOT ROLLED STEEL
- PILOT POINT: ASTM A575- \langle LATEST REVISION \rangle 1-1/4 $^{\prime}$ DIAMETER HOT ROLLED STEEL BAR.
- BOLTS: ROUND HEAD REQULAR SQAURE NECK CARRIAGE BOLT, 1-8UNC-2A PER ANSI B18.5, SAE J429 GRADE 5.
- NUTS: HEAVY HEX NUT PER ASTM A194 GRADE 2H OR ASTM A563 GRADE DH, MEETING SUPPLEMENTARY REQQUIREMENTS OF ASTM A563, 1-8UNC-2B PER ANSI B18. 2. 2.
- <u>i</u> BASEPLATE IS PERMANENTLY STAMPED WITH MANUFACTURER'S IDENTIFICATION "ABC" IN 1/2" LETTERS AND DATE CODE IN 1/4" LETTERS.

 BASEPLATE PERMANENTLY MARKED TO INDICATE CABLEVAY OPENING IN SHAFT.

