



- FINISH: HOT DIP GALVANIZE PER ASTM-A153 (LATEST REVISION).
 BASEPLATE TO BE PERPENDICULAR TO SHAFT AXIS (±1°) AND HOLE
 CENTERLINE CONCENTRIC (±, 188) TO SHAFT AXIS.
 STENCIL MIN. 1/2 IN. LETTERS MANUFACTURER'S NUMBER
 AFTER GALVANIZING.
 PILOT POINT AND SHAFT AXES TO BE CONCENTRIC (±, 125 FIM) AND
 IN LINE (±2°).

- FLAME CUT TWO SLOTS IN SHAFT PERPENDICULAR TO THE BASEPLATE. PREHEAT, TUMBLEBLAST, HANDGRIND, AND CLEAN BASEPLATE, PREHEAT, TUMBLEBLAST, HANDGRIND, AND CLEAN BASEPLATE, PREHEAT, TUMBLEBLAST, HANDGRIND, AND CLEAN BASEPLATE, PREHEAT, TO BELOW NOT TO ALL WELDED AREAS.

 HELIX, AND PILOT POINT ON ALL WELDED AREAS.

 FLAMECUT IRREGULARITIES PERMISSIBLE: (1) VALLEYS NOT TO EXCEED 3/32 IN. ABOVE NOMINAL SURFACE IRREGULARITIES NOT TO EXCEED 1/32 IN. ABOVE NOMINAL SURFACE LEVEL OR INTERSECTIONS OF NOMINAL SURFACES.

 MANUFACTURER TO HAVE IN EFFECT INDUSTRY RECOGNIZED WRITTEN QUALITY CONTROL FOR ALL MATERIALS AND MANUFACTURING PROCESSES.

 ALL MATERIAL IS TO BE NEW, UNUSED AND MILL TRACEABLE MEETING THE FOLLOWING SPECIFICATIONS:

BASEPLATE: ASTM A36-(LATEST REVISION) HOT ROLLED STEEL PLATE

SHAFT: STEEL PIPE PILES, SEAMLESS OR STRAIGHT WELDED, GRADE-2 PER ASTM A252. ALT. MATERIAL: STEEL PIPE TYPE E OR S, GRADE-B PER ASTM A53.

HELLIX: ASTM A29-(LATEST REVISION) $3/8^{\prime}$ THICK HOT ROLLED STEEL PLATE OR COIL.

BOLT: HEX HEAD MACHINE BOLT 1-8UNC, PER ANSI B. 18, 2, 1, SAE J429 GRADE 5 PILOT POINT: ASTM A107-(LATEST REVISION) 1-1/4" DIAMETER HOT ROLLED STEEL

- <u>10</u> BASPLATE IS PERMANENTLY STAMPED WITH MANUFACTUREER'S IDENTIFICATION "ABC" IN 1/2" LETTERS AND DATE COND IN 1/4" LETTERS.

 BASEPLATE PERMANENTLY MARKED TO INDICATE CABLEWAY OPENING IN SHAFT.

CHANCE

7

ALL RADIAL SECTIONS

88

PITCH



SHEET 1/1

m 🖁

7112-0363

HELIX MUST BE FORMED BY MATCHING METAL DIE

ALL RAJI NJRMAL

RADIAL SECTIONS

ž